

# Global Manufacturing- Greenfield Flex Conduit



## Features

Our Global Manufacturing Greenfield Flex Conduit is a non-jacketed flexible steel conduit which has many universal wiring applications. It is often referred to as Reduced Wall Flex. Our Greenfield varies in sizes from 3/8" - 4" and is offered in varying quantities between 25' and 1000'. Non-UL.



## Sizing and Features

Product	Size	Description	Qty	Inner Diameter		Outer Diameter	
				Min.	Max.	Min.	Max.
GF0375-100	3/8"	NON-UL Greenfield Flex Conduit	100	.374	.376	.555	.571
GF0375-250	3/8"	NON-UL Greenfield Flex Conduit	250	.374	.376	.555	.571
GF0375-1000	3/8"	NON-UL Greenfield Flex Conduit	1000	.374	.376	.555	.571
GF0500-100	1/2"	NON-UL Greenfield Flex Conduit	100	.618	.634	.850	.866
GF0500-500	1/2"	NON-UL Greenfield Flex Conduit	500	.618	.634	.850	.866
GF0500-1000	1/2"	NON-UL Greenfield Flex Conduit	1000	.618	.634	.850	.866
GF0750-100	3/4"	NON-UL Greenfield Flex Conduit	100	.827	.846	1.043	1.063
GF0750-500	3/4"	NON-UL Greenfield Flex Conduit	500	.827	.846	1.043	1.063
GF1000-50	1"	NON-UL Greenfield Flex Conduit	50	1.039	1.059	1.280	1.299
GF1000-100	1"	NON-UL Greenfield Flex Conduit	100	1.039	1.059	1.280	1.299
GF1000-400	1"	NON-UL Greenfield Flex Conduit	400	1.039	1.059	1.280	1.299
GF1250-50	1-1/4"	NON-UL Greenfield Flex Conduit	50	1.319	1.343	1.512	1.535
GF1250-250	1-1/4"	NON-UL Greenfield Flex Conduit	250	1.319	1.343	1.512	1.535
GF1500-25	1-1/2"	NON-UL Greenfield Flex Conduit	25	1.496	1.520	1.827	1.850
GF1500-150	1-1/2"	NON-UL Greenfield Flex Conduit	150	1.496	1.520	1.827	1.850
GF2000-25	2"	NON-UL Greenfield Flex Conduit	25	2.047	2.075	2.335	2.362
GF2000-100	2"	NON-UL Greenfield Flex Conduit	100	2.047	2.075	2.335	2.362
GF2500-25	2-1/2"	NON-UL Greenfield Flex Conduit	25	2.520	2.559	2.913	2.953
GF3000-25	3"	NON-UL Greenfield Flex Conduit	25	3.071	3.110	3.465	3.504
GF3500-25	3-1/2"	NON-UL Greenfield Flex Conduit	25	3.504	3.551	3.909	3.957
GF4000-25	4"	NON-UL Greenfield Flex Conduit	25	4.094	4.154	4.449	4.508

- Crush and corrosion resistant steel for lasting mechanical protection
- Steel Construction
- Hot Dip Galvanized Zinc Coating
- Smooth interior for easy wire pull through
- For use as an electrical raceway in close quarters requiring extra flexibility