Global Manufacturing-Greenfield UL Flex Conduit



Features

Our Global Manufacturing Greenfield Flex Conduit is a non-jacketed flexible conduit has many universal wiring applications. It is often referred to as Reduced Wall Flex. Our Greenfield varies in sizes from 3/8"- 4" and is offered in varying quantities between 25' and 1000'.



| Sizing and Features | | | | Inner Diameter | | Outer Diameter | |
|---------------------|--------|----------------------------|------|----------------|-------|----------------|-------|
| Product | Size | Description | Qty | Min. | Max. | Min. | Max. |
| GFUL0375-100 | 3/8" | UL Greenfield Flex Conduit | 100 | .484 | .504 | .689 | .709 |
| GFUL0375-250 | 3/8" | UL Greenfield Flex Conduit | 250 | .484 | .504 | .689 | .709 |
| GFUL0375-1000 | 3/8" | UL Greenfield Flex Conduit | 1000 | .484 | .504 | .689 | .709 |
| GFUL0500-100 | 1/2" | UL Greenfield Flex Conduit | 100 | .622 | .642 | .819 | .839 |
| GFUL0500-1000 | 1/2" | UL Greenfield Flex Conduit | 1000 | .622 | .642 | .819 | .839 |
| GFUL0750-100 | 3/4" | UL Greenfield Flex Conduit | 100 | .815 | .835 | 1.032 | 1.051 |
| GFUL0750-500 | 3/4" | UL Greenfield Flex Conduit | 500 | .815 | .835 | 1.032 | 1.051 |
| GFUL1000-50 | 1" | UL Greenfield Flex Conduit | 50 | 1.032 | 1.055 | 1.287 | 1.315 |
| GFUL1000-400 | 1" | UL Greenfield Flex Conduit | 400 | 1.032 | 1.055 | 1.287 | 1.315 |
| GFUL1250-50 | 1 1/4" | UL Greenfield Flex Conduit | 50 | 1.370 | 1.394 | 1.630 | 1.661 |
| GFUL1250-250 | 1 1/4" | UL Greenfield Flex Conduit | 250 | 1.370 | 1.394 | 1.630 | 1.661 |
| GFUL1500-25 | 1 1/2" | UL Greenfield Flex Conduit | 25 | 1.579 | 1.598 | 1.866 | 1.902 |
| GFUL1500-150 | 1 1/2" | UL Greenfield Flex Conduit | 150 | 1.579 | 1.598 | 1.866 | 1.902 |
| GFUL2000-25 | 2" | UL Greenfield Flex Conduit | 25 | 2.020 | 2.043 | 2.339 | 2.374 |
| GFUL2000-50 | 2" | UL Greenfield Flex Conduit | 50 | 2.020 | 2.043 | 2.339 | 2.374 |
| GFUL2000-100 | 2" | UL Greenfield Flex Conduit | 100 | 2.020 | 2.043 | 2.339 | 2.374 |
| GFUL2500-25 | 2-1/2" | UL Greenfield Flex Conduit | 25 | 2.480 | 2.504 | 2.839 | 2.874 |
| GFUL3000-25 | 3" | UL Greenfield Flex Conduit | 25 | 3.070 | 3.098 | 3.460 | 3.500 |
| GFUL3500-25 | 3-1/2" | UL Greenfield Flex Conduit | 25 | 3.550 | 3.576 | 3.950 | 3.995 |
| GFUL4000-25 | 4" | UL Greenfield Flex Conduit | 25 | 4.000 | 4.039 | 4.457 | 4.500 |

- Crush and corrosion resistant steel core for lasting mechanical protection
- Used for Outdoor installations
- High mechanical strength
- •Temperature range is from -15° C +70° C

