

Global Manufacturing- Liquid-Tite Non-Metallic



Features

Our Global Manufacturing Liquid-Tite is designed for use in continuous-flex applications. It is flexible and features an inner core with woven nylon mesh reinforcement. Our Non-Metallic Liquid-Tite varies in sizes from 1/2" - 2" and is offered in varying quantities between 50' and 1000'. It also comes available in a carton or in a full reel.



Sizing and Features

Product	Size	Description	Qty	Inner Diameter		Outer Diameter	
				Min.	Max.	Min.	Max.
DC0500-100	1/2"	Non-Metallic DC Class, Carton	100	.622	.642	.820	.840
DC0500-1000	1/2"	Non-Metallic DC Class, Reel	1000	.622	.642	.820	.840
DC0750-100	3/4"	Non-Metallic DC Class, Carton	100	.820	.840	1.030	1.050
DC0750-800	3/4"	Non-Metallic DC Class, Reel	800	.820	.840	1.030	1.050
DC1000-100	1"	Non-Metallic DC Class, Carton	100	1.041	1.066	1.290	1.315
DC1000-500	1"	Non-Metallic DC Class, Reel	500	1.041	1.066	1.290	1.315
DC1250-100	1-1/4"	Non-Metallic DC Class, Carton	100	1.380	1.410	1.630	1.660
DC1500-050	1-1/2"	Non-Metallic DC Class, Carton	50	1.575	1.600	1.865	1.900
DC2000-050	2"	Non-Metallic DC Class, Carton	50	2.020	2.045	2.340	2.375

- Resists corrosion, abrasion, oil, water, acid, metal shavings, and rough environments
- UL Type B flexible nonmetallic liquidtight conduit
- Suitable for Indoor or Outdoor Use
- Integral Rigid and flexible PVC Construction

UL TYPE B FLEXIBLE NONMETALLIC LIQUIDTIGHT CONDUIT DETAILS

- 1/2" through 2" trade sizes
- Use with top-flex nylon connectors straight or right angle
- May also be used with Die-Cast Connectors for liquidtight conduit
- Resists corrosion, abrasion, oil, water, acid, metal shavings, and rough environments
- Resists abuse, pull, and crushing
- Smooth interior for easier wire pulling, no hazardous sharp edges or burrs; will not damage conductors
- For direct burial/poured concrete
- Lightweight and lower installed cost

- Quick installation; cuts with utility knife or PVC Cutter
- Integral Rigid or flexible PVC Construction
- Suitable for Indoor/Outdoor Use:
 - HVAC Equipment
 - Machine Tools
 - Motors and Controls
 - Marine Equipment
 - Pumps Refrigeration Equipment
- UV Rated
- Withstands up to 80° C

