

Global Manufacturing- Liquid-Tite Steel Core EF Class



Features

Our Global Manufacturing Liquid-Tite is designed for use in continuous flex applications. It is flexible and features an inner core with woven nylon mesh reinforcement. Our Steel Core EF Class Liquid-Tite varies in sizes from 3/8" - 4" and is offered in varying quantities between 25' and 1000'. It also comes available in a carton or in a full reel.

Sizing and Features

Product	Size	Description	Qty	Inner Diameter		Outer Diameter	
				Min.	Max.	Min.	Max.
EF0375-100	3/8"	Steel Core EF Class, Carton	100	.484	.504	.690	.710
EF0375-1200	3/8"	Steel Core EF Class, Reel	1200	.484	.504	.690	.710
EF0500-100	1/2"	Steel Core EF Class, Carton	100	.622	.642	.820	.840
EF0500-500	1/2"	Steel Core EF Class, Reel	500	.622	.642	.820	.840
EF0500-1000	1/2"	Steel Core EF Class, Reel	1000	.622	.642	.820	.840
EF0750-100	3/4"	Steel Core EF Class, Carton	100	.820	.840	1.030	1.050
EF0750-500	3/4"	Steel Core EF Class, Reel	500	.820	.840	1.030	1.050
EF0750-1000	3/4"	Steel Core EF Class, Reel	1000	.820	.840	1.030	1.050
EF1000-100	1"	Steel Core EF Class, Carton	100	1.041	1.066	1.290	1.315
EF1000-400	1"	Steel Core EF Class, Reel	400	1.041	1.066	1.290	1.315
EF1250-050	1-1/4"	Steel Core EF Class, Carton	50	1.380	1.410	1.630	1.660
EF1250-250	1-1/4"	Steel Core EF Class, Reel	250	1.380	1.410	1.630	1.660
EF1500-050	1-1/2"	Steel Core EF Class, Carton	50	1.575	1.600	1.865	1.900
EF1500-200	1-1/2"	Steel Core EF Class, Reel	200	1.575	1.600	1.865	1.900
EF2000-050	2"	Steel Core EF Class, Carton	50	2.020	2.045	2.340	2.375
EF2000-100	2"	Steel Core EF Class, Reel	100	2.020	2.045	2.340	2.375
EF2500-025	2-1/2"	Steel Core EF Class, Carton	25	2.480	2.505	2.840	2.875
EF3000-025	3"	Steel Core EF Class, Carton	25	3.070	3.100	3.460	3.500
EF3500-025	3-1/2"	Steel Core EF Class, Carton	25	3.500	3.535	3.720	3.812
EF4000-025	4"	Steel Core EF Class, Carton	25	4.000	4.040	4.460	4.500

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through
- For use in damp or wet locations, suitable for commercial or industrial use.
- Material: EF PVC Jacketed Steel Core Coil wrapped in clear plastic shrink wrap